

Lingeling and Friends Entering the SAT Race 2015

Armin Biere

Institute for Formal Models and Verification

Johannes Kepler University Linz

Abstract—This is a solver description for our SAT solvers Lingeling, Treengeling and Plingeling entering the SAT Race 2015. We only focus on the difference to their 2014 versions. For further information we refer to previous solver descriptions [1], [2], [3], our POS'14 talk [4] and of course the source code.

BASE VERSION

Two versions of Lingeling are submitted to the main sequential track of the SAT Race. The base version *bal* differs from the SAT competition 2014 version described in [3] as follows. The most important difference is due to adopting a variant of the Glucose restart scheme [5], which proved very effective on the SAT Competition 2014 benchmarks, particularly for small time limits, as our post-competition analysis showed.

A detailed evaluation of these changes related to restarts can be found in [6]. Further changes consist of adding a quaternary resolution inprocessor, similar to but much more conservative in adding quaternary resolvents than the previously existing ternary resolution component. The data structure for decision variable selection has been split into the original binary heap and an additional queue holding variables with a score of zero (initially or after rescoring). This reduces time spent in bumping variables etc. An extensive discussion of CDCL variable scoring schemes and their efficient implementation can be found in our SAT'15 conference paper [7].

Certain benchmarks in the SAT Competition 2014 turned out to have a 'lucky phase' solution, e.g., for instance can be solved by setting all variables to false. The previous version of Lingeling missed these simple solutions, since more advanced phase initialization heuristics force some variables to be set to true. This made these instances very hard to solve for Lingeling in contrast to all the MiniSAT and Glucose variants used in the competition, which find the solution without producing any conflict. Even though we consider the inclusion of these benchmarks in the 2014 competition set as highly problematic, we implemented a simple *lucky phase checker* which detects this situation and initializes phases accordingly.

Finally we added a poor man's version of SAT sweeping. It uses similar refinement techniques as our more effective solution [8] based on blocked clause decomposition [8], [9], but it is easier to integrate and can be used during inprocessing [10]. Equivalent literal candidate pairs are checked in the same way as in [8]. However, if all variables in clauses containing those literals or their negations are assigned and propagated without leading to a conflict, this partial model is used for refining equivalence classes, while [8] uses full models.

Supported by FWF, NFN Grant S11408-N23 (RiSE).

PARAMETER TUNING

Version *baq* of Lingeling starts to explore techniques for automatic parameter selection in the spirit of portfolio solving, which explicitly was allowed in the SAT Race 2015. This is mainly motivated by results reported in [6], which clearly show that different restart intervals can have a huge impact on solving speed. Even though sophisticated dynamic restart schemes are useful in general, see again [6] for an extensive discussion, they still fail on certain instances, where either a faster or slower restart frequency would be much better. We observed, that these intervals often can be picked optimally for certain benchmark families, called *buckets* in [11].

Thus we added a simple classification scheme based on a *k*-nearest neighbor (KNN) algorithm, which predicts the origin of a benchmark (more precisely the SAT competition 2014 bucket). It uses the number of variables and clauses (of different length) of the original and simplified instance after one round of pre-/inprocessing. We generated optimized binary KNN classifiers using different *k*'s and features for each individual bucket. If the classifiers disagree the base version is used. Otherwise we pick the restart interval or other parameter settings determined to be best for the predicted bucket in separate experiments.

In these experiments with the base version *bal*, we used the same set of parameter value choices as in Plingeling. To avoid exploring all combinations of parameter settings only one parameter setting was chosen to be different from the base version in each experiment, similar to how parameters are set for individual solver instances in Plingeling. Not all buckets lead to parameter changes, nor are all investigated parameter settings used.

Parameter tuning is disabled in the parallel front-ends Plingeling and Treengeling. However, Plingeling uses those new 13 different parameter settings for individual solver threads. Otherwise there is no difference compared to the 2014 version. The same applies to Treengeling. A failed attempt to make use of portfolio solving within a Cube-And-Conquer solver is included in the code but disabled.

LICENSE

The default license of Lingeling, Treengeling and Plingeling applies to these SAT Race 2015 versions as well. It allows the use of the software for academic, research and evaluation purposes. It further prohibits the use of the software in other competitions or similar events without explicit written permission. Please refer to the actual license, which comes with the source code, for more details, or contact the author.



REFERENCES

- [1] A. Biere, “Lingeling and friends entering the SAT Challenge 2012,” in *Proceedings SAT Challenge 2012: Solver and Benchmark Descriptions*, ser. Department of Computer Science Series of Publications B, A. Balint, A. Belov, D. Diepold, S. Gerber, M. Jarvisalo, and C. Sinz, Eds., vol. B-2012-2. University of Helsinki, 2012, pp. 33–34.
- [2] —, “Lingeling, Plingeling and Treengeling entering the SAT Competition 2013,” in *Proc. of SAT Competition 2013*, ser. Department of Computer Science Series of Publications B, University of Helsinki, A. Belov, M. Heule, and M. Jarvisalo, Eds., vol. B-2013-1, 2013, pp. 51–52.
- [3] —, “Yet another local search solver and Lingeling and friends entering the SAT Competition 2014,” ser. Department of Computer Science Series of Publications B, A. Belov, M. J. H. Heule, and M. Jarvisalo, Eds., vol. B-2014-2. University of Helsinki, 2014, pp. 39–40.
- [4] —, “Lingeling essentials, A tutorial on design and implementation aspects of the the SAT solver lingeling,” in *POS-14. Fifth Pragmatics of SAT workshop, a workshop of the SAT 2014 conference, part of FLoC 2014 during the Vienna Summer of Logic, July 13, 2014, Vienna, Austria*, ser. EPIC Series, D. L. Berre, Ed., vol. 27. EasyChair, 2014, p. 88.
- [5] G. Audemard and L. Simon, “Refining restarts strategies for SAT and UNSAT,” in *Principles and Practice of Constraint Programming - 18th International Conference, CP 2012, Québec City, QC, Canada, October 8-12, 2012. Proceedings*, ser. Lecture Notes in Computer Science, M. Milano, Ed., vol. 7514. Springer, 2012, pp. 118–126.
- [6] A. Biere and A. Fröhlich, “Evaluating CDCL restart schemes,” 2015, submitted.
- [7] —, “Evaluating CDCL variable scoring schemes,” in *Theory and Applications of Satisfiability Testing - SAT 2015, 18th International Conference, SAT 2015, Austin, Texas, USA, September 24-27, 2015, Proceedings (to appear)*, 2015.
- [8] M. Heule and A. Biere, “Blocked clause decomposition,” in *Logic for Programming, Artificial Intelligence, and Reasoning - 19th International Conference, LPAR-19, Stellenbosch, South Africa, December 14-19, 2013. Proceedings*, ser. Lecture Notes in Computer Science, K. L. McMillan, A. Middeldorp, and A. Voronkov, Eds., vol. 8312. Springer, 2013, pp. 423–438.
- [9] T. Balyo, A. Fröhlich, M. Heule, and A. Biere, “Everything you always wanted to know about blocked sets (but were afraid to ask),” in *Theory and Applications of Satisfiability Testing - SAT 2014 - 17th International Conference, Held as Part of the Vienna Summer of Logic, VSL 2014, Vienna, Austria, July 14-17, 2014. Proceedings*, ser. Lecture Notes in Computer Science, C. Sinz and U. Egly, Eds., vol. 8561. Springer, 2014, pp. 317–332.
- [10] M. Jarvisalo, M. Heule, and A. Biere, “Inprocessing rules,” in *Automated Reasoning - 6th International Joint Conference, IJCAR 2012, Manchester, UK, June 26-29, 2012. Proceedings*, ser. Lecture Notes in Computer Science, B. Gramlich, D. Miller, and U. Sattler, Eds., vol. 7364. Springer, 2012, pp. 355–370.
- [11] A. Belov, M. J. H. Heule, and M. Jarvisalo, Eds., *Proc. of SAT Competition 2014*, ser. Department of Computer Science Series of Publications B, vol. B-2014-2. University of Helsinki, 2014.